

定速压缩机 -R22(1φ-50Hz-220/240V)

FIXED FREQUENCY COMPRESSOR

系列 Series	代表机型 Typical Model	排量 Displ. (cm ³ /rev)	制冷量 Cooling Capacity (W) (Btu/h)	功率 Power (W)	能效比 COP (W/W)	电容 Capacitor (μF/V)	压缩机高度 Compressor Height (mm)	排气管内径 Discharge Pipe ID (mm)	回气管内径 Suction Pipe ID (mm)	备注 Remark
--------------	-----------------------	--	---	--------------------	---------------------	---------------------------	------------------------------------	------------------------------------	----------------------------------	--------------

R22

1φ-50Hz-220/240V

测试条件 Test Condition: ASH

GO	PH60G0C-4BZDE	6.0	985	3361	345	2.86	20/370	241	6.5	9.8	----
	PH104G0C-4BZDE	10.4	1745	5954	580	3.01	25/370	259	6.5	9.8	----
	PH108G0C-4BZDE	10.8	1830	6244	590	3.10	25/370	259	6.5	9.8	----
SN	HSN82V1UBZ	8.2	1455	4964	485	3.00	25/370	251	6.5	9.8	----
M1	PH130M1C-4DZDE2	13.1	2225	7592	725	3.07	25/370	270	9.8	6.5	----
G1	PH135G1C-4DZDE1	13.3	2270	7745	725	3.13	30/370	285	9.8	8.2	----
SM	HSM150V4UDZ	15.1	2680	9144	885	3.03	30/370	292	8.1	12.9	----
	HSM165V3UDZ	16.4	2865	9775	910	3.15	30/370	292	8.1	9.8	----
	HSM180V3UDZ	17.9	3138	10708	996	3.15	30/370	292	8.1	9.8	▲
	HSM200V3UDZ	20.1	3525	12027	1175	3.00	35/370	301	9.8	12.9	----
	HSM215V2UDZ	21.4	3700	12624	1175	3.15	35/370	301	9.8	12.9	----
	HSM215V2UFT	21.4	3700	12624	1175	3.15	35/370	301	9.8	12.9	----
	HSM215V3UDZ	21.4	3700	12624	1215	3.05	35/370	301	8.2	12.9	----
M2	HSM215V3UFT	21.4	3700	12624	1215	3.05	35/370	301	8.2	12.9	----
	PH225M2A-4FT	22.4	3915	13357	1285	3.10	35/400	293	8.2	12.9	----
	PH240M2A-4FT1	24.0	4195	14346	1353	3.10	35/400	293	8.2	12.9	----
	PH290M2A-4FT1	28.8	5090	17367	1650	3.08	35/370	348	9.8	12.9	----
	PH295M2AS-4KUH1	29.7	5350	18253	1715	3.12	45/370	348	9.8	12.9	----
G2	PH310M2AS-4KTH	31.0	5585	18988	1750	3.18	44/370	348	9.8	12.9	----
	PH320M2AS-4KUH	31.0	5610	19141	1781	3.15	45/370	348	9.8	12.9	▲
	PH300G2C-4KU1	29.8	5340	18220	1645	3.25	55/400	297	9.8	12.9	----
	PH310G2C-4KU1	30.8	5515	18817	1695	3.25	55/400	310	9.8	12.9	----
	PH340G2C-4KU1	33.7	6030	20574	1865	3.23	60/400	310	9.8	12.9	----
G2	PH340G2C-4KU	33.7	6050	20643	1805	3.35	60/400	310	9.8	12.9	----
	PH360G2C-4MU1	36.0	6475	22093	2005	3.23	50/400	324	9.8	16.2	----
	PH370G2CS-4MU1	37.0	6650	22690	2065	3.22	50/400	324	9.8	16.2	----
	PH370G2C-4MU	37.0	6660	22724	2020	3.30	50/400	324	9.8	16.2	----
	PH400G2CS-4MU1	39.8	7100	24225	2225	3.15	50/400	354	9.8	16.2	----
	PH400G2CS-4MU	39.8	7095	24208	2215	3.20	50/400	354	9.8	16.2	----
	PH420G2CS-4KU1	42.0	7420	25317	2390	3.10	50/400	354	9.8	12.9	----
	PH420G2CS-4MU	42.0	7555	25778	2365	3.20	50/400	354	9.8	16.2	----
	PH440G2CS-4MU	43.6	7810	26648	2390	3.27	50/400	354	9.8	16.2	----
	X3	PH460X3CS-4MU1	45.9	8060	27501	2600	3.10	55/400	397	9.8	16.2
PH480X3CS-4MU1		47.9	8460	28866	2730	3.10	55/400	397	9.8	16.2	----

定速压缩机-R22(1φ-60Hz-208/230V)&R22(1φ-60Hz-115V)

FIXED FREQUENCY COMPRESSOR

系列 Series	代表机型 Typical Model	排量 Displ. (cm ³ /rev)	制冷量 Cooling Capacity (W)	功率 Power (W)	能效比 COP (W/W)	电容 Capacitor (μF/V)	压缩机高度 Compressor Height (mm)	排气管内径 Discharge Pipe ID (mm)	回气管内径 Suction Pipe ID (mm)	备注 Remark
--------------	-----------------------	--	--------------------------------	--------------------	---------------------	---------------------------	---------------------------------------	---------------------------------------	-------------------------------------	--------------

R22

1φ-60Hz-208/230V

测试条件 Test Condition: ASH

SN	HSN98N1UBR	9.8	2075	7080	645	3.22	15/370	251	8.1	9.8	----
	HSN102N1VBZ	10.2	2100	7165	665	3.16	15/370	251	8.1	9.8	----
GO	PH108G0C-3BZDU	10.8	2200	7506	710	3.10	25/370	259	6.5	9.8	----
M1	PH120M1C-3DZDU1	12.2	2490	8496	790	3.15	30/370	266	8.2	9.8	----
	PH130M1C-3DZDU1	13.1	2660	9076	850	3.13	30/370	270	8.5	9.8	----
G1	PH140G1C-3DZDU1	13.9	2890	9861	895	3.23	35/370	285	8.2	9.8	----
	PH150G1C-3DZDU2	15.1	3135	10697	990	3.17	35/370	285	8.2	9.8	----
	PH160G1C-3DZDU1	16.0	3280	11191	1015	3.23	35/370	285	8.2	9.8	----
	PH165G1C-3FZDU1	16.5	3475	11857	1060	3.28	40/370	285	8.2	9.8	----
SM	HSM170N2UDZ	17.0	3495	11925	1075	3.25	40/370	292	8.1	9.8	----
G1	PH175G1C-3FTU	17.6	3710	12659	1140	3.25	35/370	294	8.2	12.9	----
	PH180G1C-3FTU1	18.1	3800	12966	1195	3.18	40/370	292	8.2	12.9	----
	PH195G1C-3FTU1	19.6	4155	14090	1310	3.17	35/370	292	8.2	12.9	----
M2	PH210M2A-3FT	20.9	4575	14090	1345	3.40	45/370	292	8.2	12.9	▲
	PH225M2C-3FTU1	22.4	4770	16275	1505	3.17	40/370	292	8.2	12.9	----
	PH240M2A-3FTU1	23.9	5140	17538	1580	3.25	40/370	292	8.2	12.9	----
	PH250M2A-3FTU2	25.0	5400	18425	1685	3.20	40/370	333	9.8	12.9	----
X2	PH260M2AS-3KUU1	26.1	5625	19193	1815	3.10	40/400	333	9.8	12.9	----
	PH260X2C-3FTU1	29.0	6130	20916	1990	3.08	50/370	311	9.8	12.9	----

1φ-60Hz-208/230V

G2	PH310G2C-3KUU	31.0	6700	22860	2000	3.35	55/400	310	9.8	12.9	----
	PH330G2C-3MUU	32.8	7150	24396	2135	3.35	55/400	297	9.8	16.2	----
	PH330G2C-3MUU1	32.8	7040	24020	2215	3.18	55/400	297	9.8	16.2	----
	PH340G2C-3MUU	33.7	7340	25044	2190	3.35	55/400	297	9.8	16.2	----
	PH340G2C-3MUU1	33.7	7280	24839	2275	3.20	55/400	297	9.8	16.2	----
	PH360G2C-3KUU1	36.0	7685	26221	2405	3.20	55/400	310	9.8	12.9	----
X3	PH370G2C-3MUU1	37.0	8020	27364	2505	3.20	55/400	310	9.8	16.2	----
	PH401X3CS-3MUU	40.2	8745	29840	2690	3.25	60/400	372	9.8	16.2	----
	PH441X3CS-3MUU	43.5	9470	32312	2915	3.25	60/400	372	9.8	16.2	----

1φ-60Hz-208/230V

测试条件 Test Condition: GX

SM	HSM145N1VDT	14.5	3400	11601	800	4.25	35/370	292	8.1	9.8	▲
----	-------------	------	------	-------	-----	------	--------	-----	-----	-----	---

1φ-60Hz-115V

测试条件 Test Condition: ASH

M1	EH130M1C-1DZDU1	13.1	2700	9212	850	3.17	45/250	266	8.2	9.8	----
	EH170M1B-1DZ1	16.8	3500	11942	1120	3.13	55/250	285	8.2	9.8	----