

Model: RG5492W-FZ4A
Product Description

Type:	Rotary Compressors
Application:	HBP/AC - Air Conditioning
ProductDescription:	R-22/R-407C
Voltage/Frequency:	220-240V ~ 50Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	220V ~ 50HZ	6000	1512	1759	650	9.23	2.33	2.71	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

General

Evaporating Temp. Range:	-23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	0
Weight Unit of Measure:	
Displacement (cc):	12.742
Oil Type:	Polyvinylether
Viscosity (cSt):	68
Oil Charge (cc):	290

Electrical

Voltage Range (50 Hz):	198-253
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	16
Rated Load Amps (RLA 50 Hz):	3.15
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	4.76

Motor Resistance (Ohm) - Start:
Motor Type:

10.28
CSR

Overload Type:

Relay Type:

Agency Approval

CE Listed, VDE Listed